



ORLEN OIL GEAR CVT

General characteristics:

Synthetic transmission oil for a wide range of vehicles equipped with CVT (Continuous Variable Transmission), with belts and chains. Provides long life of the transmission, stable viscosity, and optimal power transfer.

Application:

ORLEN OIL GEAR CVT is suitable for various types of vehicle makes equipped with CVT type transmission. The CVT design differs greatly from the traditional automatic stepped transmission (for example, systems that generate metal-to-metal contact contain metal-belts and a pulley), so for the CVT transmission, you should not use traditional oils for automatic transmission. Suitable for use in cars made by various manufacturers, including: VW/Audi, BMW, Ford, GM, Renault, Nissan, Mitsubishi, Toyota, Honda, Hyundai, and others, where the manufacturer recommends the use of a CVT type oil. The oil should not be mixed with other transmission oils.

Specifications:

VW/Audi TL 521 16 (G 052 516), 521 80 (G 052 180 A2), Renault CVT CK/SK/FK, BMW Minicooper EZL 799A/83 22 0 136 376/83 22 0 429 154, 799/EZL, 799A/ZF, CVT V1, Audi Multitronic, Toyota CVFT TC, FE, GM/Saturn DEX-CVT, Hyundai/Kia CVT-1, SP III, HONDA HMMF, HCF2, Z-1 (poza Honda Fit & Jazz rok. prod. 2001-2007), Suzuki CVTF TC, 3320, 4401, NS-2, Green 1&2, Green 1V, Mazda JWS 3320, Volvo CVT 4959, Chery CVT, Daihatsu AMMIX CVT Fluid DFE, DC, DFC, TC, Dodge/Jeep/Chrysler NS-2, Dodge/Jeep/Chrysler/Mopar CVT + 4, Fiat Tutela CVT N.G, Fujijyuuko i-CVTF FG, Idemitsu CVTF-EX1, Lexus Fluid TC, FE, MG Rover EM-CVT, Mitsubishi CVTF-1, CVTF-J4/J4+, CVTF Eco J4, SP-III, Nissan KTF-1, NS-1, NS-2, NS-3, Punch CVTF-EX1, Subaru iCVT, iCVT FG, ECVT, CVT II Fluid, K0425Y0710 & K0425Y0711, HT CVT Fluid, CV-30, K0421Y0700, NS-2

Physical and chemical parameters:

Parameters	Units	Typical values
Kinematic viscosity at 100°C	mm ² /s	7.5
Viscosity index	-	170
pour point max	°C	- 42
flash point min.	°C	200
Brookfield viscosity at -40°C	mPa*s	10,510

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

V2 / 2024-04-30