



ORLEN OIL AGRO SUPREME 10W-40

General features

Semisynthetic multi-grade UHPDO engine oil designed for naturally aspirated and turbo-charged diesel engines. It is recommended for tractors and agricultural machinery operated in extreme conditions.

Guarantee:

- longer oil change intervals;
- maximised engine output in extreme conditions;
- improved fuel management;
- prevention from soot deposits.

Application

ORLEN OIL Agro Supreme 10W-40 is a multi-grade engine oil intended for lubrication of naturally aspirated and turbo-charged diesel engines.

Recommended for use in tractors, combines and other agricultural machinery with this viscosity and quality grade specified by manufacturers. It ensures effective engine lubrication event at continuous reverse operation mode. It is suitable for engines meeting the emission standards. It is a good choice for agricultural machinery engines operated on farms with large crop areas under extreme load and machinery used on small and large farms, as well as for municipal works and landscape maintenance. It can be used in vehicles meeting EPA Tier 2 and EPA Tier 1, if all requirements of the vehicle manufacturer for quality and viscosity grades are met.

Quality class

API: CI-4

ACEA: E4, E7

Viscosity grad

SAE: 10W-40

Standards, approvals, specifications

DTFR 15B120 (228.5),
MAN M3277,
VOLVO VDS-3,
MACK EO-N,
RENAULT VI RLD-2.

Meets requirements:

DEUTZ DQC-III-18;
MTU Type 2,
MTU Type 3,
MAN 3275,
Volvo VDS 2,
Cummins CES 20078

Physical and chemical properties

Parameters	Unit	Typical values
SAE viscosity grade	-	10W-40
Kinematic viscosity at 100 °C	mm ² /s	14,1
Viscosity index	-	140
Flow temperature	°C	-41
Flash point	°C	240
TBN base number	mg KOH/g	10,1

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

V2 / 2024-05-20