

ORLEN OIL CLASSIC LIFE+ 20W-50

General features

Oil ORLEN OIL Classic Engine Life+ 20W-50 is a multigrade mineral oil, made to protect engines with significant progress, petrol and diesel engines. Carefully selected additives allow keeping sludge in the form of suspension, which is particularly important in the case of worn-out units. The formula "Reduce Oil Consumption" helps reducing leaks and oil consumption.

Guarantees:

- · Maintaining engine cleanliness
- · Reduction of oil refills
- Protecting the most vulnerable parts of the engine

Application

Oil ORLEN OIL Classic Life + 20W-50 is made primarily to protect the engines with milage higher than 150 000 km. With carefully chosen formulation is ideal for use in structures tending to increased oil consumption.

Quality class API: SG/CF-4

Viscosity grad SAE: 20W-50

Physical and chemical properties

Parameters	Unit	Typical values
SAE Viscosity index	-	20W-50
Kinematic viscosity at temperature 100 °C	mm2/s	19,04
Viscosity index	-	139
Flow temperature	°C	-21
Flash-point	°C	234
Total base number	Mg KOH/g	9,6
Sulphated ash	%	1,25
Noack volatility	% (m/m)	7,3

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

v. 2 /2024.03.07